

## 4" Fouling Resistant Spiral Wound Elements

### Description:

Low Pressure, High Productivity:

The FR type membrane surface is more hydrophilic due to the special treatment. It is specially designed for water treatment against biological and organic fouling. With build-in FR properties, this model of elements allows for effective cleaning, renewing active membrane surface thus extending the service life in the tough water conditions.


### Specifications:

Model	Permeate Flow GPD(m <sup>3</sup> /day)	Active Membrane Area ft <sup>2</sup> (m <sup>2</sup> )	Stabilized Salt Rejection	Minimum Salt Rejection	Feed spacer mil(mm)	Test Conditions
FR- 4040	2400(9.1)	90(8.4)	99.6%	99.4%	28(0.7)	225psi/2000ppm NaCl

1. All performance data are collected at 25°C (77°F), pH7.5 and 8% recovery rate.
2. Permeate flows for single element may vary ±15%.

### Element Dimension:

\* Unit: Inch (mm)  
1 inch= 25.4 mm



**Operating Limits  
for Design:**

Maximum Operating Temperature.....	45°C(113°F)
Maximum Operating Pressure.....	600psi(41bar)
Maximum Pressure Drop (single element).....	15psi(1.0bar)
pH Range for Continuous Operation.....	2-11
pH Range for Cleaning.....	1.2-12
Chlorine tolerance.....	<0.1ppm
Maximum Feed SDI.....	5

